

# Checkmarq BOS-1500

## DATASHEET



### FEATURES

- Eliminate costly unscheduled patching
- Eliminate attacks on vulnerable applications and operating systems
- Malware detection (bi-directional)
- Increase internal bandwidth (removing unwanted traffic)
- Overall cost reduction
  - Less ad-hoc patching
  - Less insurance cost
  - Less time for reporting
  - No hands on action for updating system
  - No extra support costs

### Performance

Aggregate Throughput	200 megabits per second
Typical Latency	< 100 microseconds
Total Sessions	2.500.000
Connections Per Second	> 100.000

### Scalability

Two 10/100 Ethernet ports
Copper
1 segment
1 management port

### Power supply

Units	1x AC
Watts (max)	200
Volts	100/240
Amps (max)	2/0,9
Frequency range (Hz)	50-60

### Cooling system

1x 4cm ø fan for system cooling

### Dimensions

Rack form factor	1U
Height (inches)	1,71
Height (cm)	4,34
Width (inches)	16,8
Width (cm)	42,67
Depth (inches)	14,4
Depth (cm)	36,58

### Certification

CE/FCC/UL

### BOS-1500 competitive advantages

- Performance advantage over other intrusion prevention systems
- Bi-directional intrusion prevention engine stops malware
- Ease-to-use, easy to install
- Simple and obvious web interface

### World-class technical support

- Checkmarq offers worldwide support for all BOS-models
- Online support: support@checkmarq.net
- Worldwide Technical support number: +31 70 30 98 800
- Warranty service: +31 70 30 98 812

